



collingwood



Quick and easy installation with bespoke wall plug



2W at 350mA



IP65 ideal for outdoor areas

MC020 S

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	200g
Inrush Current	N/A
Cut Out Size	20
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3

Guarantee

Warranty 7 years

Features & benefits

- Bi-directional mini cube for discreet accent lighting of interior and exterior spaces
- Quality brushed aluminium finish
- Requires 20mm drill bit

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC020 S NW	Silver	2W	4000K	12°	140	70	1485	
MC020 S WW	Silver	2W	3000K	12°	110	55	1466	
MC020 S 27	Silver	2W	2700K	12°	107	54	1425	
MC020 S RED	Silver	2W	Red	12°				

Wiring Information

Cable / Flying Lead	0.15m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m(0.205 mm ² red&blackPTFE)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately

33x33/29.5mm

