

# MC020 S

Up / down mini cuboid LED wall light

#### FEATURES

- IP rating CSP Switchable Tiltable (°) Dimmable Option LED Lifetime Colour Rendering Index Colour Consistency Rotation angle (°)
- IP65 Single CCT Fixed Driver dependent L70 70,000h CRI>80 SDCM3 360

### INSTALLATION INFORMATION

350mA DC Input Maximum Ambient Temperature 35°C 200g Weight Inrush Current N/A Cut Out Size 20 **Construction Material** Anodised aluminium UK Bathroom Zone 1 Electric Class (1, 2, 3) Ш **Mounting Options** Wall

#### PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC020 S NW	Silver	2W	4000K	12°	140	70	1485	A F
MC020 S WW	Silver	2W	3000K	12°	110	55	1466	A F
MC020 S RED	Silver	2W	Red	12°				

Energy rating is a reflection of the LED light source.

#### WIRING INFORMATION

Cable / Flying Lead	0.15m (0.205mm <sup>2</sup> red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m(0.205 mm² red&blackPTFE)

#### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	1	1	8

#### ACCESSORIES CR135

PDC/GRID DIMMER UY2 CONNECTOR PTFE cable Grid dimmer kit for multiple fitting types Quick waterproof connector Sold Separately Sold Separately Sold Separately



#### LIGHTING INNOVATION

ß

IP**65** 

Quick and easy installation with bespoke wall plug

2W at 350mA

IP65 ideal for outdoor areas

## WARRANTY

7 ye

## FEATURES & BENEFITS

Bi-directional mini cube for discreet accent lighting of interior and exterior spaces Quality brushed aluminium finish Requires 20mm drill bit

c	<u>33x33/29.5mm</u>
58mm	