



MC020 S

Up / down mini cuboid LED wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	200g
Inrush Current	N/A
Cut Out Size	20
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MC020 S NW	Silver	2W	4000K	12°	140	70	1485	
MC020 S WW	Silver	2W	3000K	12°	110	55	1466	
MC020 S 27	Silver	2W	2700K	12°	107	54	1425	
MC020 S RED	Silver	2W	Red	12°				

Wiring Information

Cable / Flying Lead	0.15m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m(0.205 mm ² red&blackPTFE)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



collingwood



Quick and easy installation with bespoke wall plug



2W at 350mA



IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

- Bi-directional mini cube for discreet accent lighting of interior and exterior spaces
- Quality brushed aluminium finish
- Requires 20mm drill bit

