

MF02 IP

Adjustable LED mini light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	45
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	360

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	90g
Inrush Current	N/A
Cut Out Size	N/A
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Mounting Options	Wall

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MF02 IP NW	Silver	1W	4000K	16°	66	66	452	A F
MF02 IP WW	Silver	1W	3000K	16°	53	53	252	A F
MF02 IP RED	Silver	1W	Red	16°				

WIRING INFORMATION

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m (0.205mm² red & black PTFE)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

WB/M 01 / WB/M 02	Single bracket / double bracket	Sold Separately
CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION



360° wall light perfect for various applications



1W at 350mA



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Mini spot light for discreet illumination

/ year warrant

