

# MF02 IP

Features	
IP rating	IP65
CSP Switchable	Single CCT
Tiltable	45°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information				
Input	350mA			
Maximum Ambient Temperature	35°C			
Weight	90g			
Inrush Current	N/A			
Cut Out Size	N/A			
Construction Material	Stainless steel (316)			
UK Bathroom Zone	1			
Electric Class (1, 2, 3)	3			

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MF02 IP NW	Silver	1W	4000K	16°	66	66	452	A F
MF02 IP WW	Silver	1W	3000K	16°	53	53	252	A F
MF02 IP 27	Silver	1W	2700K	16°	52	52	245	A t G
MF02 IP RED	Silver	1W	Red	16°				

## **Wiring Information**

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	0.15m (0.205mm² red & black PTFE)

#### **LED Driver**

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

#### **Accessories**

WB/M 01 / WB/M 02	Single bracket / double bracket	Sold Separately
CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately

# collingwood



360° wall light perfect for various applications



1W at 350mA




IP65 ideal for outdoor areas

#### Guarantee

Warranty 7 years

#### Features & benefits

- Mini spot light for discreet illumination
- 7 year warranty



cologgwoodled



ngwoodlighting