

ML01

Decorative LED mini light

FEATURES

IP rating	IP68
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	50g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes
Mounting Options	Wall

PHOTOMETRICS @ 25°C

Product code	w	Colour	lm	lm/W	Energy
ML01 NW	1W	4000K	4	4	A A G
ML01 WW	1W	3000K	3.6	3	A A G
ML0127	1W	2700K	3.5	3.5	A f G

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm² red&blackPTFE)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV350700TD (350 & 500mA)	220-240V	Yes	Yes	N/A		
PSIP3509W	220-240V	Yes	No	0	1	8

ACCESSORIES

UY2 CONNECTOR	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION



Coastal protected



1W at 350mA



IP68 ideal for outdoor areas and extreme weather

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Small & discreet decorative recessed LED light

Perfect for discreet decorative light in interior and exterior applications

