

# ML01

Decorative LED mini light

#### **FEATURES**

IP rating	IP68	
CSP Switchable	Single CCT	
Tiltable	No	
Dimmable Option	Driver dependent	
LED Lifetime	L70 70,000h	
Colour Rendering Index	CRI>80	
Colour Consistency	SDCM3	
Rotation Angle	No	

#### INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	35°C
Weight	50g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	lm	lm/W
ML01 NW		1W	4000K	4	4
ML01 WW		1W	3000K	3.6	3
ML0127		1W	2700K	3.5	3.5
ML01 RED	Silver	1W	Red		

Energy rating is a reflection of the LED light source.

## WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm² red&blackPTFE)

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PSIP3509W	220-240V	Yes	No	0	1	8
PSMD35039	220-240V	Yes	Yes (mains)	0	3	9

### **ACCESSORIES**

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION



Coastal protected



1W at 350mA



IP68 ideal for outdoor areas and extreme weather

### WARRANTY

Warranty

7 years

### FEATURES & BENEFITS

Small & discreet decorative recessed LED light

Perfect for discreet decorative light in interior and exterior applications

