

ML02

Decorative LED mini light

FEATURES

IP rating	IP68
CSP Switchable	Single CCT
Tiltable	No
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

INSTALLATION INFORMATION

Input	350mA
Maximum Ambient Temperature	35°C
Weight	90g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	lm	lm/W	Lx @ 1m	Energy
ML02 WW	Silver	1W	3000K	24	24	3	A f G

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm² red&blackPTFE)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP3509W	220-240V	Yes	No	0	1	8
PSMD35039	220-240V	Yes	Yes (mains)	0	3	9

ACCESSORIES

CR135	PTFE cable	Sold Separately		
UY2 CONNECTOR	Quick waterproof connector	Sold Separately		



LIGHTING INNOVATION



Coastal protected



1W at 350mA



IP68 ideal for outdoor areas and extreme weather

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Great for guidance lighting

Small & discreet decorative LED light

Raised profile creates diffused glow effect on surrounding surface

