

# ML02

Decorative LED mini light

#### **FEATURES**

IP rating	IP68
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

## INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	35°C
Weight	90g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes
Mounting Options	Wall

# PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	lm	lm/W	Lx @ 1m	Energy
ML02 WW	Silver	1W	3000K	24	24	3	A t G

#### WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm² red&blackPTFE)

#### LED DRIVER

DRV150700 220-240V Yes N/A	
PSIP3509W 220-240V Yes No 0 1	1 8

#### **ACCESSORIES**

CR135	PTFE cable	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



LIGHTING INNOVATION



Coastal protected



1W at 350mA



IP68 ideal for outdoor areas and extreme weather

### WARRANTY

Warranty

7 years

#### FEATURES & BENEFITS

Great for guidance lighting

Small & discreet decorative LED light

Raised profile creates diffused glow effect on surrounding surface

