



ML02

Decorative LED mini light

Features

IP rating	IP68
CSP Switchable	Single CCT
Tiltable	No
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	50g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Stainless steel (316)
UK Bathroom Zone	0
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	W	Colour	lm	lm/W	Lx @ 1m	Energy
ML02 NW	Silver	1W	4000K	35	35	4	
ML02 WW	Silver	1W	3000K	24	24	3	
ML02 27	Silver	1W	2700K	23	23	3	
ML02 RED	Silver	1W	Red				

Wiring Information

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm ² red&blackPTFE)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	0	1	9
PSIP3509W	220-240V	Yes	No	0	1	8
PSMD35039	220-240V	Yes	Yes (mains)	0	3	9

Accessories

CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



collingwood



Coastal protected



1W at 350mA



IP68 ideal for outdoor areas and extreme weather

Guarantee

Warranty 7 years

Features & benefits

- Great for guidance lighting
- Small & discreet decorative LED light
- Raised profile creates diffused glow effect on surrounding surface

