

ML03

Mini halo LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tiltable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	30°C
Weight	60g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes
Mounting Options	Wall

PHOTOMETRICS @ 25°C

Product code	Finish	w	Colour	lm	lm/W	Lx @ 1m	Energy
ML03 NW	Silver	1W	4000K	40	40	4	A G F
ML03 WW	Silver	1W	3000K	28	28	3	A F
ML03 RED	Silver	1W	Red				

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm² red & black PTFE)		
Type of Wiring Required	Series		
Input Cable Type	(0.205 mm² red&blackPTFE)		

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

ACCESSORIES	
CR135	PTFE cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
UY2 CONNECTOR	Quick waterproof connector



LIGHTING INNOVATION



Coastal protected



1W at 350mA



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Raised profile creates diffused glow effect on surrounding surface

Small, discreet and low glare decorative LED light

