



Coastal protected

1W

1W at 350mA

IP65

IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Raised profile creates diffused glow effect on surrounding surface

Small, discreet and low glare decorative LED light

ML03

Mini halo LED wall light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	Fixed
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA DC
Maximum Ambient Temperature	30°C
Weight	60g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	III
Suitable for coastal areas	Yes
Mounting Options	Wall

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	lm	lm/W	Lx @ 1m	Energy
ML03 NW	Silver	1W	4000K	40	40	4	
ML03 WW	Silver	1W	3000K	28	28	3	
ML03 RED	Silver	1W	Red				

WIRING INFORMATION

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm ² red&blackPTFE)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP3509W	220-240V	Yes	No	1	1	8

ACCESSORIES

CR135	PTFE cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
UY2 CONNECTOR	Quick waterproof connector

