



ML03

Mini halo LED wall light

Features

IP rating	IP65
CSP Switchable	Single CCT
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

Installation Information

Input	350mA
Maximum Ambient Temperature	30°C
Weight	60g
Inrush Current	N/A
Cut Out Size	26
Construction Material	Anodised aluminium
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	W	Colour	lm	lm/W	Lx @ 1m	Energy
ML03 NW	Silver	1W	4000K	40	40	4	
ML03 WW	Silver	1W	3000K	28	28	3	
ML03 BLUE	Silver	1W	Blue	-	-	-	
ML03 RED	Silver	1W	Red	-	-	-	
ML03 27	Silver	1W	2700K	27	27	3	

Wiring Information

Cable / Flying Lead	1m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm ² red&blackPTFE)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

CR135	PTFE cable
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
UY2 CONNECTOR	Quick waterproof connector



collingwood



Coastal protected



1W at 350mA



IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

- Raised profile creates diffused glow effect on surrounding surface
- Small, discreet and low glare decorative LED light

