

MS02 IP



Installation Information				
Input	350mA			
Maximum Ambient Temperature	35°C			
Weight	90g			
Inrush Current	N/A			
Cut Out Size	N/A			
Construction Material	Stainless steel (316)			
UK Bathroom Zone	1			
Electric Class (1, 2, 3)	3			

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MS02 IP NW	Silver	1W	4000K	12°	73	73	2160	A F
MS02 IP WW	Silver	1W	3000K	12°	50	50	2000	A F
MS02 IP 27	Silver	1W	2700K	12°	49	49	1944	A F
MS02 IP BLUE	Silver	1W	Blue	12°				
MS02 IP RED	Silver	1W	Red	12°				

Wiring Information

Cable / Flying Lead	0.15m (0.205mm² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm² red&blackPTFE)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

WB/M 01 / WB/M 02	Single bracket / double bracket	Sold Separately
CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately

collingwood



360° wall light perfect for various applications



1W at 350mA




IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

• Mounting plates available



congwoodlighting