



MS02 IP

Adjustable LED mini light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	45°
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	350mA
Maximum Ambient Temperature	35°C
Weight	90g
Inrush Current	N/A
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MS02 IP NW	Silver	1W	4000K	12°	73	73	2160	
MS02 IP WW	Silver	1W	3000K	12°	50	50	2000	
MS02 IP 27	Silver	1W	2700K	12°	49	49	1944	
MS02 IP BLUE	Silver	1W	Blue	12°	-	-	-	
MS02 IP RED	Silver	1W	Red	12°	-	-	-	

Wiring Information

Cable / Flying Lead	0.15m (0.205mm ² red & black PTFE)
Type of Wiring Required	Series
Input Cable Type	(0.205 mm ² red&blackPTFE)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PSIP3509W	220-240V	Yes	No	1	1	8
PSMD35039	220-240V	Yes	Yes (mains)	1	3	9

Accessories

WB/M 01 / WB/M 02	Single bracket / double bracket	Sold Separately
CR135	PTFE cable	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
UY2 CONNECTOR	Quick waterproof connector	Sold Separately



collingwood



360° wall light perfect for various applications



1W at 350mA



IP65 ideal for outdoor areas

Guarantee

Warranty 7 years

Features & benefits

- Mounting plates available

