



360° wall light perfect for various applications



1W at 350mA



IP65 ideal for outdoor areas

## WARRANTY

Warranty

7 years

## FEATURES & BENEFITS

Mounting plates available



## MS02 IP

Adjustable LED mini light

### FEATURES

<b>IP rating</b>	IP65
<b>CSP Switchable</b>	Single CCT
<b>Tilttable (°)</b>	45
<b>Dimmable Option</b>	Driver dependent
<b>LED Lifetime</b>	L70 70,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM3
<b>Rotation angle (°)</b>	360

### INSTALLATION INFORMATION

<b>Input</b>	350mA DC
<b>Maximum Ambient Temperature</b>	35°C
<b>Weight</b>	90g
<b>Inrush Current</b>	N/A
<b>Cut Out Size</b>	N/A
<b>Construction Material</b>	Stainless steel (316)
<b>UK Bathroom Zone</b>	1
<b>Electric Class (1, 2, 3)</b>	III
<b>Mounting Options</b>	Wall

### PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
MS02 IP NW	Silver	1W	4000K	12°	73	73	2160	
MS02 IP WW	Silver	1W	3000K	12°	50	50	2000	
MS02 IP 27		1W	2700K	12°	49	49	1944	
MS02 IP RED	Silver	1W	Red	12°				

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.15m (0.205mm <sup>2</sup> red & black PTFE)
<b>Type of Wiring Required</b>	Series
<b>Input Cable Type</b>	(0.205 mm <sup>2</sup> red&blackPTFE)

### LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP3509W	220-240V	Yes	No	1	1	8

### ACCESSORIES

<b>WB/M 01 / WB/M 02</b>	Single bracket / double bracket	Sold Separately
<b>CR135</b>	PTFE cable	Sold Separately
<b>PDC/GRID DIMMER</b>	Grid dimmer kit for multiple fitting types	Sold Separately
<b>UY2 CONNECTOR</b>	Quick waterproof connector	Sold Separately

