



Colour switchable between 2700k, 3000k, & 4000k



Energy efficient up to 138lm/W



Available with DALI-2, 1-10V & PUSH-DIM



## NOVA CSP

### FEATURES

<b>IP rating</b>	IP40
<b>IK rating</b>	IK06
<b>CSP Switchable</b>	Switchable CCT
<b>UGR</b>	UGR<19
<b>Sensor Option</b>	On Request
<b>Dimmable Option</b>	Yes (DALI-2, 1-10V, PUSH-DIM)
<b>LED Lifetime</b>	L70 50,000h
<b>Colour Rendering Index</b>	CRI>80
<b>Colour Consistency</b>	SDCM5
<b>Emergency Option</b>	Yes, remotely using Salvus Route

### INSTALLATION INFORMATION

<b>Input</b>	220-240V AC
<b>Maximum Ambient Temperature</b>	-20°C - 50°C
<b>Weight</b>	3.8kg
<b>Inrush Current</b>	4.9A 154ms
<b>Construction Material</b>	Aluminium housing, Microprism lens
<b>Electric Class (1, 2, 3)</b>	2
<b>Install Connector Type</b>	Push-fit terminals 0,5 - 1,5mm <sup>2</sup>
<b>UK Building Regulations</b>	Part P & L
<b>Power Factor</b>	0.95

### WARRANTY

Warranty	5 years
On-Site Warranty	2 years

### FEATURES & BENEFITS

- Wide light emitting surface designed for superior optical control and comfortable light
- Makes rooms appear larger and wider
- Floating impression when surface-mounted
- Design-led pendant can be centrepiece of any room
- Wall mounted creates interest
- 450mm and 600mm can be wall mounted
- 4000K for focus scenes - 3000K for social scenes - 2700K for relaxation

### Photometrics @ 25°C

Product Code	Finish	Type	Beam	W	Colour	lm	lm/W	Energy
NVB45DS	Black - gold	450mm	120°	26W	2700K	2600	100	
					3000K	2800	108	
					4000K	3000	115	
NVB60DS	Black - gold	600mm	120°	40W	2700K	4200	117	
					3000K	4500	125	
					4000K	4800	133	
NVB90DS	Black - gold	900mm	120°	68W	2700K	7900	122	
					3000K	8300	128	
					4000K	9000	138	
NVW45DS	White - gold	450mm	120°	26W	2700K	2600	108	
					3000K	2800	117	
					4000K	3000	125	
NVW60DS	White - gold	600mm	120°	40W	2700K	4200	117	
					3000K	4500	125	
					4000K	4800	133	
NVW90DS	White - gold	900mm	120°	68W	2700K	7900	122	
					3000K	8300	128	
					4000K	9000	138	

### WIRING INFORMATION

<b>Cable / Flying Lead</b>	0.75-1.5mm <sup>2</sup>
<b>Type of Wiring Required</b>	Parallel

### ACCESSORIES

<b>NV45UPM</b>	Nova Uplight Kit, 450mm, 13W 1100lm, On-Off, 3000K	Sold Separately
<b>NV60UPM</b>	Nova Uplight Kit, 600mm, 20W 1700lm, On-Off, 3000K	Sold Separately





**COLLINGWOOD**  
LIGHTING

LIGHTING INNOVATION

Designer light that can be surface mounted to create a floating effect, suspended to be a centrepiece of a room or wall mounted to create interest. Colour switchable as standard, Nova as be a cool 4000K white, neutral 3000K or warm and inviting 2700K.

<b>NV90UPM</b>	Nova Uplight Kit, 900mm, 28W 2400lm, On-Off, 3000K	Sold Separately
<b>NVBSUS2M</b>	Nova Pendant Kit Black, 2 metres, 5 core cable	Sold Separately
<b>NVWSUS2M</b>	Nova Pendant Kit White, 2 metres, 5 core cable	Sold Separately
<b>EMRBST</b>	Salvus Route Black, Self Test, Open Corridor Lens	Sold Separately
<b>EMRWST</b>	Salvus Route White, Self Test, Open Corridor Lens	Sold Separately