



LUXI 54

Rectangular terminal bollard

FEATURES

| | |
|------------------------|-------------|
| IP rating | IP54 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Sensor Option | No |
| Dimmable Option | No |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM6 |

INSTALLATION INFORMATION

| | |
|-----------------------------|--------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 40°C |
| Weight | 2.130 |
| Inrush Current | N/A |
| Construction Material | Aluminium |
| UK Bathroom Zone | N/A |
| SELV | No |
| Electric Class (1, 2, 3) | I |
| Suitable for coastal areas | No |

PHOTOMETRICS @ 25°C

| Product code | Finish | W | Colour | Beam | lm | lm/W | Energy |
|--------------|----------------------------|----|--------|------|-----|------|--------|
| OU13624 | Anthracite grey RAL7016 | 7W | 3000K | 90° | 750 | 75 | |

WIRING INFORMATION

| | |
|------------------------------|------------------------------------|
| Cable / Flying Lead | cable diameter for connection 12mm |
| Cable Required for Connector | max. cable diameter 12mm |
| Type of Wiring Required | Parallel |

LED DRIVER

| Driver | Input | SELV | Dimming | Bathroom Zone |
|--------------------------|----------|------|---------|---------------|
| N/A (intergrated driver) | 220-240V | No | N/A | N/A |

ACCESSORIES

N/A (No Accessories required)

7W 7W

IP54 IP54 ideal for walk ways and step lighting

CRI>80 CRI 80 providing true colour appearance

WARRANTY

Warranty 3 years

FEATURES & BENEFITS

IK08 for robust impact protection

Great for soft illumination onto stone paths

Anthracite RAL 7016

BEAM ANGLE: 90°

