



LUXI 650

Straight to mains bollard

FEATURES

IP rating	IP54
IK rating	IK06
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 40°C
Weight	2.000
Inrush Current	N/A
Construction Material	Cast Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	I
Suitable for coastal areas	No

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Energy
OUI3824	Anthracite grey RAL7016	7W	3000K	30°	660	68	

WIRING INFORMATION

Cable / Flying Lead	cable diameter for connection 12mm
Cable Required for Connector	max. cable diameter 12mm
Type of Wiring Required	Parallel

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (intergrated driver)	220-240V	No	N/A	N/A

ACCESSORIES

N/A (No Accessories required)



COLLINGWOOD
LIGHTING

LIGHTING INNOVATION

7W 7W

IP54 IP54 ideal for walk ways and step lighting

CRI>80 CRI 80 providing true colour appearance

WARRANTY

Warranty 3 years

FEATURES & BENEFITS

IK06 for robust impact protection

Great for soft illumination onto stone paths

Anthracite RAL 7016

BEAM ANGLE: 30°

