



BASIL 1 P

4W LED spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	360°
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 50°C
Weight	0.454kg
Inrush Current	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Energy
OU517WW05	Black	4W	3000K	50°	295	74	

Wiring Information

Cable / Flying Lead	Cable 1.0-2.5mm ² , AWG 17-14
Type of Wiring Required	Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (driver built in)	220-240V	No	N/A	1



collingwood



3 x 4W



360° tilt for maximum flexibility



IP65 ideal for outdoor areas

Guarantee

Warranty 5 years

Features & benefits

- Maximum rotation function for directing light precisely where it is required
- High efficacy of 75lm/W
- Elegant and discreet black finish