



## BASIL 2 P

2x4W LED spike light

### Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	360°
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	360°

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 50°C
Weight	0.66kg
Inrush Current	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
SELV	No
Electric Class (1, 2, 3)	2

### Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Energy
OU518WW05	Black	2x4W	3000K	50°	2x295	74	

### Wiring Information

Cable / Flying Lead	Cable 1.0-2.5mm <sup>2</sup> , AWG 17-14
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (driver built in)	220-240V	No	N/A	1



collingwood

4W

2 x 4W

360°

360° tilt for maximum flexibility

IP65

IP65 ideal for outdoor areas

### Guarantee

Warranty 5 years

### Features & benefits

- Maximum rotation function for directing light precisely where it is required
- High efficacy of 75lm/W
- Elegant and discreet black finish