Spike lights specification sheet



BASIL 3 P

Features

LED Lifetime

IP rating CSP Switchable Tiltable

3x4W LED spike light

Colour Rendering Index

Colour Consistency

Rotation Angle

	Installation Informa	ition
IP65	Input	220-240V
Single CCT	Maximum Ambient Temperature	-20°C - 50°
360°	Weight	0.866kg
L70 50,000h	Inrush Current	N/A
CRI>80	Construction Material	Aluminium
SDCM3	UK Bathroom Zone	N/A
360°	SELV	No
	Electric Class (1, 2, 3)	2

Photometrics @ 25°C

Product Code	Finish	w	Colour	Beam	lm	lm/W	Energy
OU519WW05	Black	3x4W	3000K	50°	3x295	74	A G E

Wiring Information

Cable / Flying Lead Type of Wiring Required Cable 1.0-2.5mm², AWG 17-14 Parallel

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone
N/A (driver built in)	220-240V	No	N/A	1

collingwood

4₩

4W



in collingwoodlighting

© collingwoodled

360° tilt for maximum flexibility



5 years

Guarantee

Warranty

Features & benefits

- Maximum rotation function for directing light precisely where it is required
- High efficacy of 75lm/W
- Elegant and discreet black finish