



Can be used with the Collingwood landscape range

Push and 1-10V dimmable

Supplied with 1.5m synchronisation cable

## PLD UNI-DRIVE 350MA

350mA Driver

### FEATURES

<b>IP rating</b>	IP20
------------------	------

### INSTALLATION INFORMATION

<b>Maximum Ambient Temperature</b>	-25°C - 50°C
<b>Weight</b>	245g
<b>Inrush Current</b>	5A 0.05ms
<b>Construction Material</b>	Plastic
<b>UK Bathroom Zone</b>	1
<b>SELV</b>	Yes
<b>Electric Class (1, 2, 3)</b>	II
<b>DIN Rail Mount</b>	No
<b>Connection Output</b>	Terminals
<b>UK Protection</b>	Short circuit, overload & overheating
<b>Power Factor</b>	0.98

### Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
N/A	0.14	110-240V AC	350mA	2-46	0.98


### WIRING INFORMATION

<b>Input Cable Type</b>	0.5-1.5mm <sup>2</sup> max.
<b>Output Cable Type</b>	0.5-1.5mm <sup>2</sup> max.

103mm



22mm



67mm