## Wiring & drivers specification sheet



# PLU/350 1-9

350mA Driver

| Features  |      |
|-----------|------|
| IP rating | IP20 |
|           |      |

| Installation Information    |                           |  |  |  |
|-----------------------------|---------------------------|--|--|--|
| Maximum Ambient Temperature | 40°C                      |  |  |  |
| Weight                      | 80g                       |  |  |  |
| Double Insulation           | Yes                       |  |  |  |
| Inrush Current              | 25.5A 0.6ms               |  |  |  |
| Construction Material       | Plastic                   |  |  |  |
| UK Bathroom Zone            | 1                         |  |  |  |
| SELV                        | SELV                      |  |  |  |
| Electric Class (1, 2, 3)    | 2                         |  |  |  |
| Connection Output           | Terminals                 |  |  |  |
| UK Protection               | Short circuit, overload & |  |  |  |
|                             | overheating               |  |  |  |
| Power Factor                | 0.55                      |  |  |  |

## **Electrical Characteristics**

| Driver Rated Wattage | Driver Input<br>Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|-------------------------|----------------------|---------------|-----------------------|--------------|
| N/A                  | 0.14A                   | 220-240V AC          | 350mA         | 3-27V                 | 0.55         |

### **Wiring Information**

| •                 |             |
|-------------------|-------------|
| Input Cable Type  | 1.5mm² max. |
| Output Cable Type | 1.5mm² max. |

### **Accessories**

| IX 265 PLU weatherproof housing |  |
|---------------------------------|--|
|---------------------------------|--|



Ideal for use with the Collingwood landscape range

IP20 rated

350mA

#### Guarantee

Warranty 1 year

## Features & benefits

