



Ideal for use with the Collingwood landscape range

IP40 rated

350mA

PLU/PP/350 1-9

350mA Driver

Features

| | |
|-----------|------|
| IP rating | IP20 |
|-----------|------|

Installation Information

| | |
|-----------------------------|---------------------------------------|
| Maximum Ambient Temperature | 40°C |
| Weight | 104g |
| Double Insulation | Yes |
| Inrush Current | 25.5A 0.6ms |
| Construction Material | Plastic |
| UK Bathroom Zone | 1 |
| SELV | SELV |
| Electric Class (1, 2, 3) | 2 |
| Connection Output | Terminals |
| UK Protection | Short circuit, overload & overheating |
| Power Factor | 0.55 |

Guarantee

| | |
|----------|--------|
| Warranty | 1 year |
|----------|--------|

Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|----------------------|---------------|-----------------------|--------------|
| N/A | 0.14A | 220-240V AC | 350mA | 3-27V | 0.55 |

Wiring Information

| | |
|-------------------|-------------------------|
| Input Cable Type | 1.5mm ² max. |
| Output Cable Type | 1.5mm ² max. |

Accessories

| | |
|--------------------|----------------------------------|
| LED LYTE 1M EXT | 1m plug & play extension lead |
| LED LYTE 6 WAY EXT | 6-way plug & play extension lead |

Features & benefits

