



PS250600MA

one4all design DALI-2, Push-dim, 0-10V

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	170g
Insulation Coverable	No
Inrush Current	40A 0.35ms
Construction Material	Polycarbonate
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	II
Case Temperature (tc = °C)	85
Install Connector Type	Terminals 0.75-1.5mm ²
Connection Output	DC Plug and Play Connector
UK Protection	Over Voltage, Short Circuit, Thermal
Power Factor	0.95

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
25	0.18	220-240VAC, 50-60Hz	250mA - 600mA	14-42	0.95

WIRING INFORMATION

Input Cable Type	0.75 - 1.5mm ²
Output Cable Type	0.5 - 1.5mm ²

ACCESSORIES

SOLIS	PS650 compatible with SOLIS panel range	Sold Separately
DOMINO	PS650 compatible with DOMINO panel range	Sold Separately

WARRANTY

Warranty

5 years

FEATURES & BENEFITS

DALI Standard IEC 62386-101: 2014, IEC 62386-102: 2014, IEC 62386-207: 2009, DALI-2

ENEC, CE, CB approved by TUV SUD, SAA, Ctick qualified

Adjustable constant current outputs range from 250-1100mA(selectable every 50mA)

Independent ECG and with strain-relief

Built-in with permanent memory for DALI and Push-DIM, 100,000 times memory


Grow wire tested 650° for 30S and 850° for 5S

DALI 1%-100%, Push-DIM, from 100% to 1.5% dimming range

125mm



76mm



30mm