

## WARRANTY

Warranty

5 years

## FEATURES & BENEFITS

DALI Standard IEC 62386-101: 2014, IEC 62386-102: 2014, IEC 62386-207: 2009, DALI-2

ENEC, CE, CB approved by TUV SUD, SAA, Ctick qualified

Adjustable constant current outputs range from 250-1100mA(selectable every 50mA)

Independent ECG and with strain-relief

Built-in with permanent memory for DALI and Push-DIM, 100,000 times memory

Grow wire tested 650° for 30S and 850° for 5S

DALI 1%-100%, Push-DIM, from 100% to 1.5% dimming range

# PS6501100MA

Panel power supply, IP20, 40W, 750mA, DALI, 1-10V, Push-Dim

## INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 45°C
Weight	190g
Insulation Coverable	No
Inrush Current	40A 0.35ms
Construction Material	Polycarbonate
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	II
Case Temperature (tc = °C)	85
Install Connector Type	Terminals 0.75-1.5mm <sup>2</sup>
Connection Output	DC Plug and Play Connector
UK Protection	Over Voltage, Short Circuit, Thermal
Power Factor	0.95

## Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
46	0.3	220-240VAC, 50-60Hz	650mA - 1100mA	14-42	0.95

## WIRING INFORMATION

Input Cable Type	0.75 - 1.5mm <sup>2</sup>
Output Cable Type	0.5 - 1.5mm <sup>2</sup>

## ACCESSORIES

<b>SOLIS</b>	PS650 compatible with SOLIS panel range	Sold Separately
<b>DOMINO</b>	PS650 compatible with DOMINO panel range	Sold Separately

