



200W max output

IP66 rated

DALI dimmable

PSDAL20024

24V Driver

Installation Information

| | |
|-----------------------------|---------------------------------------|
| Maximum Ambient Temperature | -25°C - 50°C |
| Weight | 1800g |
| Inrush Current | 56A 640ms |
| Construction Material | Plastic |
| UK Bathroom Zone | N/A |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| DIN Rail Mount | No |
| Connection Output | Flying Lead |
| UK Protection | Short circuit, overload & overheating |
| Power Factor | 0.98 |

Guarantee

Warranty 3 years

Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|----------------------|---------------|-----------------------|--------------|
| 200W | 1.4A | 220-240V AC | 8.33A max. | 24V DC | 0.98 |

Wiring Information

| | |
|-------------------|---|
| Input Cable Type | Mains: 0.25m, 1mm ² 3-core cable Ø: 7.5mm DALI: 0.25m, 0.75mm ² 2-core cable Ø: 7mm |
| Output Cable Type | 0.25m, 1.5mm ² 2-core cable Ø 9mm |

