

WARRANTY

Warranty

3 years

PSDIP10024

24V Driver

INSTALLATION INFORMATION

| | |
|-----------------------------|---------------------------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | 40°C |
| Weight | 1200g |
| Inrush Current | 45A 0.7ms |
| Construction Material | Steel / aluminium |
| UK Bathroom Zone | N/A |
| SELV | Yes |
| Electric Class (1, 2, 3) | I |
| DIN Rail Mount | No |
| Connection Output | Flying Lead |
| UK Protection | Short circuit, overload & overheating |
| Power Factor | 0.98 |

Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|----------------------|---------------|-----------------------|--------------|
| 100 | 0.546 | 220-240V AC | 4.15A max. | 24 | 0.98 |

WIRING INFORMATION

| | |
|-------------------|--|
| Input Cable Type | Mains: 0.25m, 1mm ² 3-core cable Ø: 7.5mm 1-10V: 0.25m, 0.75mm ² 2-core cable Ø: 6.5mm |
| Output Cable Type | 0.25m, 1.5mm ² 2-core cable Ø: 7mm |

230mm



68mm