Wiring & drivers specification sheet



C collingwood

PSIP15024

24V Driver

| Features | |
|-----------|------|
| IP rating | IP67 |
| | |

| Installation Information | | | |
|-----------------------------|---------------------------|--|--|
| Maximum Ambient Temperature | 50°C | | |
| Weight | 1200g | | |
| Double Insulation | Yes | | |
| Inrush Current | 45A 1ms | | |
| Construction Material | Steel / aluminium | | |
| UK Bathroom Zone | N/A | | |
| SELV | SELV | | |
| Electric Class (1, 2, 3) | 1 | | |
| Connection Output | Flying Lead | | |
| UK Protection | Short circuit, overload & | | |
| | overheating | | |
| Power Eactor | 0.95 | | |

Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|-------------------------|----------------------|---------------|-----------------------|--------------|
| 150W | 0.80A | 220-240V AC | 6.3A max. | 24V DC | 0.95 |

Wiring Information

| _ | |
|-------------------|-----------------------------------|
| Input Cable Type | 0.25m, 1mm² 3-core cable Ø: 7.5mm |
| Output Cable Type | 0.25m, 1mm² 2-core cable Ø 8mm |

Accessories

| PDC/GRID DIMMER | Grid dimmer kit |
|-----------------|-------------------|
| PDCINT1-10V | Dimming interface |

Guarantee

Warranty 3 years

Features & benefits

