

# PSIP70018W

IP65 700mA 2W - 18W Driver

INSTALLATION INFORMATION	
Maximum Ambient Temperature	50°C
Weight	200g
Inrush Current	12A 0.1ms
Construction Material	Plastic
UK Bathroom Zone	1
SELV	Yes
Electric Class (1, 2, 3)	2
DIN Rail Mount	No
Connection Output	Flying Lead
UK Protection	Short circuit, overload & overheating
Power Factor	0.9

### **Electrical Characteristics**

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
18W	0.1A	220-240V AC	700mA	2.5 - 25V	0.9

#### WIRING INFORMATION

Input Cable Type	0.2m, 1mm² 2-core cable Ø: 7mm
Output Cable Type	0.2m, 1mm² 2-core cable Ø: 7mm



#### LIGHTING INNOVATION

IP65 rated, making it ideal for landscape products

700mA Output

Non Dimmable

## WARRANTY

Warranty

5 years

#### **FEATURES & BENEFITS**

W Min Input Wattage

BW Max Input Wattage

220-240VAC Input Voltage

Double Insulatio

Slim and discreet desigr

Easy to install with improved round cabling

149mm



37mm