

Ideal for LED strip and the
SL250 path light

30W max load

24V input

WARRANTY

Warranty

3 years

FEATURES & BENEFITS

Dimming range: 0-100%, Load: 60-100%

Protections: short circuit/ over loading /over
current

Cooling by free air convection

Flicker free

Constant Voltage

Efficiency up to 83%

PSMD3024

Mains Dimmable 30W 24V Driver

INSTALLATION INFORMATION

Input	180-240V AC
Maximum Ambient Temperature	50°C
Weight	450g
Insulation Coverable	No
Inrush Current	3A 0.08ms
Construction Material	Plastic
UK Bathroom Zone	N/A
SELV	Yes
Electric Class (1, 2, 3)	II
DIN Rail Mount	No
Install Connector Type	Terminals 0.75-4.0mm ²
Connection Output	Terminals
UK Protection	Short circuit, overload & overheating
Power Factor	0.95

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
30	0.18	180-240V AC	1.25A	24	0.95

WIRING INFORMATION

Input Cable Type	0.75-4.0mm ² max.
Output Cable Type	0.5-4.0mm ² max.

180mm



60mm