



PSMD3024

Mains Dimmable 30W 24V Driver

Features

IP rating	IP20
-----------	------

Installation Information

Input	180-240V AC
Maximum Ambient Temperature	50°C
Weight	450g
Insulation Coverable	No
Double Insulation	Yes
Inrush Current	3A 0.08ms
Construction Material	Plastic
UK Bathroom Zone	N/A
SELV	SELV
Electric Class (1, 2, 3)	2
Install Connector Type	Terminals 0.75-4.0mm ²
Connection Output	Terminals
UK Protection	Short circuit, overload & overheating
Power Factor	0.95

Electrical Characteristics

Driver Rated Wattage	Driver Input Current	Driver Input Voltage	Drive Current	Driver Output Voltage	Power Factor
30W	0.18A	180-240V AC	1.25A	24V DC	0.95

Wiring Information

Cable / Flying Lead	Terminals 0.75-4.0mm ² max.
Input Cable Type	0.75-4.0mm ² max.
Output Cable Type	0.5-4.0mm ² max.



Ideal for LED strip and the SL250 path light

30W max load

24V input

Guarantee

Warranty 3 years

Features & benefits

- Dimming range: 0-100%, Load: 60-100%
- Protections: short circuit/ over loading /over current
- Cooling by free air convection
- Flicker free
- Constant Voltage
- Efficiency up to 83%

