



## PSMD35039

350mA Driver

### Installation Information

|                             |                                       |
|-----------------------------|---------------------------------------|
| Maximum Ambient Temperature | 40°C                                  |
| Weight                      | 83g                                   |
| Inrush Current              | 33A 0.15ms                            |
| Construction Material       | Plastic                               |
| UK Bathroom Zone            | 1                                     |
| SELV                        | Yes                                   |
| Electric Class (1, 2, 3)    | 2                                     |
| Case Temperature (tc = °C)  | 80                                    |
| DIN Rail Mount              | No                                    |
| Connection Output           | Terminals                             |
| UK Protection               | Short circuit, overload & overheating |
| Power Factor                | 0.9                                   |

### Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|----------------------|----------------------|---------------|-----------------------|--------------|
| 10W                  | 0.06A                | 220-240V AC          | 350mA         | 8-28V                 | 0.9          |

### Wiring Information

|                   |                        |
|-------------------|------------------------|
| Input Cable Type  | 0.5-1.5mm <sup>2</sup> |
| Output Cable Type | 0.5-1.5mm <sup>2</sup> |



collingwood

10W rated wattage

Mains dimmable

IP20 rated

### Guarantee

Warranty 5 years

