

PSMD70024

700mA Driver

| Features | | Installation Information | | | |
|-----------|------|-----------------------------|------------|--|--|
| IP rating | IP20 | Maximum Ambient Temperature | 40°C | | |
| | | Weight | 83g | | |
| | | Double Insulation | Yes | | |
| | | Inrush Current | 31A 0.12ms | | |
| | | Construction Material | Plastic | | |
| | | UK Bathroom Zone | 0 | | |
| | | SELV | SELV | | |
| | | Electric Class (1, 2, 3) | 2 | | |
| | | Case Temperature (tc = °C) | 80 | | |
| | | Connection Output | Terminals | | |

UK Protection

Power Factor

Electrical Characteristics

| Driver Rated Wattage | Driver Input Current | Driver Input Voltage | Drive Current | Driver Output Voltage | Power Factor |
|----------------------|-------------------------|----------------------|---------------|-----------------------|--------------|
| 10W | 0.06A | 220-240V AC | 700mA | 4-14V | 0.9 |

Wiring Information

| Input Cable Type | 0.5-1.5mm ² |
|-------------------|------------------------|
| Output Cable Type | 0.5-1.5mm ² |



10W rated wattage


Mains dimmable

IP20 rated

Guarantee

Warranty 5 years

Features & benefits



Short circuit, overload &

over current