Decorative wall lights + undershelf lighting specification sheet



Plank 1

Features	
IP rating	IP20
CSP Switchable	Single CCT
Dimmable Option	Yes
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3

Installation Information			
Input	220-240V AC		
Maximum Ambient Temperature	-10°C - 30°C		
Weight	0.779kg		
Inrush Current	10A		
Construction Material	Aluminium		
UK Bathroom Zone	N/A		
Electric Class (1, 2, 3)	1		
Mounting Options	Wall		

Photometrics @ 25°C

	_						
Product Code	Finish	Туре	w	Colour	lm	lm/W	Energy
PK30/1A/3K/W	Matt white	300mm	20	3000K	1764	91	A E
PK30/1A/4K/W	Matt white	300mm	20	4000K	1957	97	A E
PK60/1A/3K/W	Matt white	600mm	40	3000K	3604	92	A E
PK60/1A/4K/W	Matt white	600mm	40	4000K	3912	100	A G E

Wiring Information

•		
Cable / Flying Lead	0.75-1.5mm2	
Type of Wiring Required	Parallel	

LED Driver

Driver	Input	Dimming	Bathroom Zone
N/A (driver built in)	220-240V	N/A	N/A

Accessories

N/A	No accessories required	







