



- IK10** IK10 for robust protection
- IP20** Perfect for internal applications
- >90Ra** CRI 90 providing true colour appearance

Plank 1

Features

IP rating	IP20
IK rating	IK10
CSP Switchable	Single CCT
Dimmable Option	Yes
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3

Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-10°C - 30°C
Weight	0.779kg
Inrush Current	10A
Cut Out Size	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	1
Mounting Options	Wall

Guarantee

Warranty 5 years

Features & benefits

- Suitable for use in sport centres, gyms or halls
- Intergal emergency option available for 600mm variant on request
- Also available in Black on request

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
PK30/1A/3K/W	Matt white	300mm	20W	3000K	110°	1764	91	
PK30/1A/4K/W	Matt white	300mm	20W	4000K	110°	1957	97	
PK60/1A/3K/W	Matt white	600mm	40W	3000K	110°	3604	92	
PK60/1A/4K/W	Matt white	600mm	40W	4000K	110°	3912	100	

Wiring Information

Cable / Flying Lead	0.75-1.5mm ²
Type of Wiring Required	Parallel

LED Driver

Driver	Input	Dimming	Bathroom Zone
N/A (intergrated driver)	220-240V	N/A	N/A

Accessories

N/A (No Accessories required)

