



## Plank 2



- IK10** IK10 for robust protection
- IP20** Perfect for internal applications
- >90Ra** CRI 90 providing true colour appearance

### Features

IP rating	IP20
IK rating	IK10
CSP Switchable	Single CCT
Dimmable Option	Yes
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>90
Colour Consistency	SDCM3

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-10°C - 30°C
Weight	0.846kg
Inrush Current	10A
Cut Out Size	N/A
Construction Material	Aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	1
Mounting Options	Wall

### Guarantee

Warranty 5 years

### Features & benefits

- Suitable for use in sport centres, gyms or halls
- Intergal emergency option available for 600mm variant on request
- Also available in Black on request

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Energy
PK30/2A/3K/W	Matt white	300mm	2x16W	3000K	110°	2x1107	93	
PK30/2A/4K/W	Matt white	300mm	2x16W	4000K	110°	2x1199	98	
PK60/2A/3K/W	Matt white	600mm	2x32W	3000K	110°	2x3035	99	
PK60/2A/4K/W	Matt white	600mm	2x32W	4000K	110°	2x3119	101	

### Wiring Information

Cable / Flying Lead	0.75-1.5mm <sup>2</sup>
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	Dimming	Bathroom Zone
N/A (intergrated driver)	220-240V	N/A	N/A

### Accessories

N/A (No Accessories required)
-------------------------------

