



## Plank 2

### Features

IP rating	IP20
CSP Switchable	Single CCT
Dimmable Option	Yes
LED Lifetime	L70 50,000h
Colour Rendering Index	CRi>90
Colour Consistency	SDCM3

### Installation Information

Input	220-240V AC
Maximum Ambient Temperature	-10°C - 30°C
Weight	0.846kg
Inrush Current	10A
Construction Material	Aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	1
Mounting Options	Wall

### Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	lm	lm/W	Energy
PK30/2A/3K/W	Matt white	300mm	2x16	3000K	2x1107	93	A t G E
PK30/2A/4K/W	Matt white	300mm	2x16	4000K	2x1199	98	A t G D
PK60/2A/3K/W	Matt white	600mm	2x32	3000K	2x3035	99	A t G E
PK60/2A/4K/W	Matt white	600mm	2x32	4000K	2x3119	101	A t G D

### Wiring Information

Cable / Flying Lead	0.75-1.5mm <sup>2</sup>
Type of Wiring Required	Parallel

### LED Driver

Driver	Input	Dimming	Bathroom Zone
N/A (driver built in)	220-240V	N/A	N/A

### Accessories

N/A	No accessories required
-----	-------------------------

**C**  
collingwood

