







POLARIS

1200mm

FEATURES

IP rating	IP66
IK rating	IK10
CSP Switchable	Single CCT
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 30°C
Weight	1kg
Inrush Current	26A 0.15ms
Construction Material	Anti-UV Polycarbonate
SELV	No
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminal, loop-
install Connector Type	in/loop-out
UK Building Regulations	Part P
Power Factor	0.9

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	w	Colour	Beam	lm	lm/W	EM lm	Lx @ 1m	Energy
POL212N	White RAL9016	Standard	34W	4000K	130°	4700	138	-	1301	A C

WIRING INFORMATION

Cable Required for Connector	0.75-2.5mm ²
Type of Wiring Required	Parallel

ACCESSORIES

N/A No accessories required



LIGHTING INNOVATION



IP66 for total dust ingress protection



IK10 rated high resistance against impact and vadalism



Tool-less installation method making for a fast installation

WARRANTY

Warrant

5 year

FEATURES & BENEFITS

Designed for industrial and residential applications

Lightweight for easy handling

Through-wired as standard so luminaires wher wired together light up as a group

Mounting brackets slide entire length of luminaire to help make refurbishment easier