


IP66 IP66 for total dust ingress protection

IK10 IK10 rated high resistance against impact and vandalism

 Tool-less installation method making for a fast installation

WARRANTY

Warranty 5 years

FEATURES & BENEFITS

Designed for industrial and residential applications

Lightweight for easy handling

Through-wired as standard so luminaires when wired together light up as a group

Mounting brackets slide entire length of luminaire to help make refurbishment easier



POLARIS

1500mm

FEATURES

| | |
|------------------------|-------------|
| IP rating | IP66 |
| IK rating | IK10 |
| CSP Switchable | Single CCT |
| UGR | UGR<22 |
| Sensor Option | No |
| Dimmable Option | No |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM5 |
| Emergency Option | No |

INSTALLATION INFORMATION

| | |
|-----------------------------|-------------------------------------|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 30°C |
| Weight | 1.1kg |
| Inrush Current | 26A 0.1ms |
| Construction Material | Anti-UV Polycarbonate |
| SELV | No |
| Electric Class (1, 2, 3) | 2 |
| Install Connector Type | Push-fit terminal, loop-in/loop-out |
| UK Building Regulations | Part P |
| Mounting Options | Ceiling |
| Power Factor | 0.9 |

WIRING INFORMATION

| | |
|------------------------------|-------------------------|
| Cable Required for Connector | 0.75-2.5mm ² |
| Type of Wiring Required | Parallel |

ACCESSORIES

| | |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|

1500mm
70.5mm
66.5mm