







POLARIS

1500mm

FEATURES

IP rating	IP66
IK rating	IK10
CSP Switchable	Single CCT
UGR	UGR<22
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC				
Maximum Ambient Temperature	-20°C - 30°C				
Weight	1.1kg				
Inrush Current	26A 0.1ms				
Construction Material	Anti-UV Polycarbonate				
SELV	No				
Electric Class (1, 2, 3)	II				
Install Connector Type	Push-fit terminal, loop-				
install Connector Type	in/loop-out				
UK Building Regulations	Part P				
Mounting Options	Ceiling				
Power Factor	0.9				

PHOTOMETRICS @ 25°C

Product code	Finish	Туре	W	Colour	Beam	lm	lm/W	EM lm	Lx @ 1m	Energy
POL115N	White RAL9016	Standard	30W	4000K	130°	4000	133	-	1113	A D

WIRING INFORMATION

Cable Required for Connector	0.75-2.5mm ²
Type of Wiring Required	Parallel

ACCESSORIES

N/A No accessories required	
-----------------------------	--



LIGHTING INNOVATION



IP66 for total dust ingress protection



IK10 rated high resistance against impact and vadalism



Tool-less installation method making for a fast installation

WARRANTY

Warranty

5 year

FEATURES & BENEFITS

Designed for industrial and residential applications

Lightweight for easy handling

Through-wired as standard so luminaires wher wired together light up as a group

Mounting brackets slide entire length of luminaire to help make refurbishment easier

1500mm

70.5mr