




IP66 IP66 for total dust ingress protection

IK10 IK10 rated high resistance against impact and vandalism

 Tool-less installation method making for a fast installation

POLARIS

1500mm

FEATURES

IP rating	IP66
IK rating	IK10
CSP Switchable	Single CCT
UGR	UGR<22
Sensor Option	No
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM5
Emergency Option	No

INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 30°C
Weight	1.1kg
Inrush Current	26A 0.1ms
Construction Material	Anti-UV Polycarbonate
SELV	No
Electric Class (1, 2, 3)	II
Install Connector Type	Push-fit terminal, loop-in/loop-out
UK Building Regulations	Part P
Mounting Options	Ceiling
Power Factor	0.9

WARRANTY

Warranty

5 years

FEATURES & BENEFITS


Designed for industrial and residential applications

Lightweight for easy handling

Through-wired as standard so luminaires when wired together light up as a group

Mounting brackets slide entire length of luminaire to help make refurbishment easier

PHOTOMETRICS @ 25°C


Product code	Finish	Type	W	Colour	Beam	lm	lm/W	EM lm	Lx @ 1m	Energy
POL115N	White RAL9016	Standard	30W	4000K	130°	4000	133	-	1113	

WIRING INFORMATION


Cable Required for Connector	0.75-2.5mm ²
Type of Wiring Required	Parallel

ACCESSORIES

N/A	No accessories required
-----	-------------------------



1500mm



70.5mm



66.5mm