



## QUBO

### FEATURES

IP rating	IP66
IK rating	IK08
CSP Switchable	Single CCT
Tilttable	120°
Sensor Option	PC Dusk to Dawn
Dimmable Option	No
LED Lifetime	L70 50,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM6
Rotation Angle	60°

### INSTALLATION INFORMATION

Input	220-240V AC
Maximum Ambient Temperature	-20°C - 30°C
Weight	QBAL: 1700g, QBAM: 700g
Inrush Current	QBAL: 12A 0.156ms, QBAM: 3.5A 0.14ms
Construction Material	Aluminium Housing, PMMA Diffuser, Grade 304 Screws
SELV	Yes
Electric Class (1, 2, 3)	1
Earth Leakage	0.1mA
Suitable for coastal areas	No

### PHOTOMETRICS @ 25°C

Product code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
QBAMN30	Anthracite grey RAL7016	Medium	10W	3000K	30°	1000	100	2141	
QBALN30	Anthracite grey RAL7016	Large	18W	3000K	30°	2000	111	4402	

### WIRING INFORMATION

Cable / Flying Lead	2m Neoprene H05RN-F 3x0.75mm <sup>2</sup> cable supplied
Type of Wiring Required	Parallel

### LED DRIVER

Driver	N/A (integrated driver)
--------	-------------------------

### ACCESSORIES

N/A	No accessories required
-----	-------------------------

**IP66** IP66 ideal for internal or external applications

**2000lm** High lumen output of up to 2000lm

**IK08** Robust impact rating of IK08

### WARRANTY

Warranty 5 years

### FEATURES & BENEFITS

Outdoor LED projector with bracket and spike for installation on floor or ground

Adjustable, rotation 0-60°, 0-120° tilt

Precision tilting degree marker on the product to facilitate orientation

Neoprene H05RN-F 2x0.75mm<sup>2</sup> cable of 2000mm

