



collingwood



Qubo

IP66

IP66 ideal for internal or external applications

2000lm

High lumen output of up to 2000lm

IK08

Robust impact rating of IK08

Features

| | |
|------------------------|-----------------|
| IP rating | IP66 |
| IK rating | IK08 |
| CSP Switchable | Single CCT |
| Tilttable | 120° |
| Sensor Option | PC Dusk to Dawn |
| Dimmable Option | No |
| LED Lifetime | L70 50,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM6 |
| Rotation Angle | 60° |

Installation Information

| | |
|-----------------------------|--|
| Input | 220-240V AC |
| Maximum Ambient Temperature | -20°C - 30°C |
| Weight | QBAL: 1700g, QBAM: 700g |
| Inrush Current | QBAL: 12A 0.156ms, QBAM: 3.5A 0.14ms |
| Construction Material | Aluminium Housing, PMMA Diffuser, Grade 304 Screws |
| SELV | Yes |
| Electric Class (1, 2, 3) | 1 |
| Earth Leakage | 0.1mA |
| Suitable for coastal areas | No |

Guarantee

Warranty 5 years

Features & benefits

- Outdoor LED projector with bracket and spike for installation on floor or ground
- Adjustable, rotation 0-60°, 0-120° tilt
- Precision tilting degree marker on the product to facilitate orientation
- Neoprene H05RN-F 2x0.75mm² cable of 2000mm

Photometrics @ 25°C

| Product Code | Finish | Type | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|----------------------------|--------|-----|--------|------|------|------|---------|--------|
| QBAMN30 | Anthracite grey RAL7016 | Medium | 10W | 3000K | 30° | 1000 | 100 | 2141 | |
| QBALN30 | Anthracite grey RAL7016 | Large | 18W | 3000K | 30° | 2000 | 111 | 4402 | |

Wiring Information

| | |
|-------------------------|--|
| Cable / Flying Lead | 2m Neoprene H05RN-F 3x0.75mm ² cable supplied |
| Type of Wiring Required | Parallel |

LED Driver

| | |
|--------|-------------------------|
| Driver | N/A (integrated driver) |
|--------|-------------------------|

Accessories

| | |
|-----|-------------------------|
| N/A | No accessories required |
|-----|-------------------------|

