



1W at 350mA or 2W at 700mA



Coastal protected



IP65 ideal for outdoor areas

WARRANTY

Warranty

7 years

FEATURES & BENEFITS

Long spike included for extra stability

Robust cable for outdoor use

Small & discreet

Single Point Source LED

SL030

1W LED spike light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	90
Dimmable Option	Driver dependent
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation angle (°)	Fixed

INSTALLATION INFORMATION

Input	350mA / 700mA DC
Maximum Ambient Temperature	35°C
Weight	433.4g
Inrush Current	N/A
Construction Material	Stainless steel (316)
UK Bathroom Zone	1
SELV	N/A
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

Photometrics @ 25°C

Product Code	Finish	Colour	Beam	W	lm	lm/W	lx @ 1m	W	lm	lm/W	lx @ 1m	Energy
				350mA				700mA				
SL030 F NW	Stainless steel 316	4000K	26°	1W	95	95	267	2W	140	70	393	
SL030 F WW	Stainless steel 316	3000K	26°	1W	75	75	210	2W	135	68	379	
SL030 F 27	Stainless steel 316	2700K	26°	1W	70	70	196	2W	120	60	337	

Energy rating is a reflection of the LED light source.

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) rubberised cable (outside diameter: 6mm)


LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700 (all settings)	220-240V	Yes	No	N/A		
DRV350700TD (700mA)	220-240V	Yes	Yes	N/A		
PSIP70018W	220-240V	Yes	No	1	1	8

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

BEAM ANGLE: 26°



Ø42mm

