

7W

Coastal protected

IP65 ideal for outdoor areas

FEATURES & BENEFITS

Long spike included for extra stability

Robust cable for outdoor use

Hooded for reduced glare

PATENT: **GB2487912 GB2512715**

SL040A

High output LED spike light

FEATURES

IP rating	IP65
CSP Switchable	Single CCT
Tilttable (°)	90
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3

INSTALLATION INFORMATION

Input	700mA DC
Maximum Ambient Temperature	35°C
Weight	600g
Inrush Current	N/A
Construction Material	Anodised aluminium
Electric Class (1, 2, 3)	III
Earth Leakage	N/A
Suitable for coastal areas	Yes

PHOTOMETRICS @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	Lx @1m	Energy
SL040A S NW	Black anodised aluminium	7W	4000K	18°	520	74	4614	
SL040A F WW	Black anodised aluminium	7W	3000K	38°	413	59	1168	
SL040A S WW	Black anodised aluminium	7W	3000K	18°	413	59	3665	
SL040A F 27	Black anodised aluminium	7W	2700K	38°	377	54	1066	
SL040A S 27	Black anodised aluminium	7W	2700K	18°	377	54	3345	

WIRING INFORMATION

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) rubberised cable (outside diameter: 6mm)

LED DRIVER

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
PLU/700 3-9	220-240V	Yes	No	1	1	9
PL/IP/700 1-3	220-240V	Yes	No	1	1	5
PLD UNI-DRIVE 700MA	220-240V	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately
PDC/GRID DIMMER	1-10V dimmer module	Sold Separately

26°