



collingwood



7W



Coastal protected



IP65 ideal for outdoor areas

SL040A

High output LED spike light

Features

IP rating	IP65
CSP Switchable	Single CCT
Tiltable	90°
LED Lifetime	L70 70,000h
Colour Rendering Index	CRI>80
Colour Consistency	SDCM3
Rotation Angle	No

Installation Information

Input	700mA
Maximum Ambient Temperature	35°C
Weight	600g
Inrush Current	N/A
Construction Material	Anodised aluminium
UK Bathroom Zone	N/A
Electric Class (1, 2, 3)	3
Earth Leakage	N/A
Suitable for coastal areas	Yes

Guarantee

Warranty 7 years

Features & benefits

- Long spike included for extra stability
- Robust cable for outdoor use
- Hooded for reduced glare

Photometrics @ 25°C

Product Code	Finish	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
SL040A S NW	Black anodised aluminium	7W	4000K	38°	520	74	4614	
SL040A F WW	Black anodised aluminium	7W	3000K	18°	413	59	1168	
SL040A S WW	Black anodised aluminium	7W	3000K	38°	413	59	3665	
SL040A F 27	Black anodised aluminium	7W	2700K	18°	377	54	1066	
SL040A S 27	Black anodised aluminium	7W	2700K	38°	377	54	3345	

Wiring Information

Cable / Flying Lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series
Input Cable Type	(H05RN-F) rubberised cable (outside diameter: 6mm)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
DRV150700	220-240V	Yes		N/A		
PSIP70018W	220-240V	Yes	No	1	1	2
PSDIM700	220-240V		Yes (1-10V)	1	1	6

Accessories

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately

