



collingwood



7W



Coastal protected



IP65 ideal for outdoor areas

SL040A

High output LED spike light

Features

| | |
|------------------------|-------------|
| IP rating | IP65 |
| CSP Switchable | Single CCT |
| Tiltable | 90° |
| LED Lifetime | L70 70,000h |
| Colour Rendering Index | CRI>80 |
| Colour Consistency | SDCM3 |

Installation Information

| | |
|-----------------------------|--------------------|
| Input | 700mA |
| Maximum Ambient Temperature | 35°C |
| Weight | 600g |
| Inrush Current | N/A |
| Construction Material | Anodised aluminium |
| Electric Class (1, 2, 3) | 3 |
| Earth Leakage | N/A |
| Suitable for coastal areas | Yes |

Photometrics @ 25°C

| Product Code | Finish | W | Colour | Beam | lm | lm/W | Lx @ 1m | Energy |
|--------------|--------------------------|----|--------|------|-----|------|---------|--------|
| SL040A S NW | Black anodised aluminium | 7W | 4000K | 38° | 520 | 74 | 4614 | |
| SL040A F WW | Black anodised aluminium | 7W | 3000K | 18° | 413 | 59 | 1168 | |
| SL040A S WW | Black anodised aluminium | 7W | 3000K | 38° | 413 | 59 | 3665 | |
| SL040A F 27 | Black anodised aluminium | 7W | 2700K | 18° | 377 | 54 | 1066 | |
| SL040A S 27 | Black anodised aluminium | 7W | 2700K | 38° | 377 | 54 | 3345 | |

Wiring Information

| | |
|-------------------------|---|
| Cable / Flying Lead | 3m H05RN-F rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series |
| Input Cable Type | (H05RN-F) rubberised cable (outside diameter: 6mm) |

LED Driver

| Driver | Input | SELV | Dimming | Bathroom Zone | Min | Max |
|---------------------|----------|------|-------------|---------------|-----|-----|
| PLU/700 3-9 | 220-240V | Yes | No | 1 | 1 | 9 |
| PL/IP/700 1-3 | 220-240V | Yes | No | 1 | 1 | 5 |
| PLD UNI-DRIVE 700MA | 220-240V | Yes | Yes (1-10V) | 2 | 1 | 10 |

Accessories

| | | |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | Waterproof junction box / Gel filled waterproof connectors | Sold Separately |
| WCR 275 BLACK | 2-core rubber cable | Sold Separately |
| PDC/GRID DIMMER | 1-10V dimmer module | Sold Separately |

Guarantee

Features & benefits

- Long spike included for extra stability
- Robust cable for outdoor use
- Hooded for reduced glare

