



# SL220A

3W LED spike light

## FEATURES

|                        |             |
|------------------------|-------------|
| IP rating              | IP65        |
| CSP Switchable         | Single CCT  |
| Tilttable              | 90°         |
| LED Lifetime           | L70 70,000h |
| Colour Rendering Index | CRI>70      |
| Colour Consistency     | SDCM3       |
| Rotation Angle         | No          |

## INSTALLATION INFORMATION

|                             |                    |
|-----------------------------|--------------------|
| Input                       | 350mA              |
| Maximum Ambient Temperature | 35°C               |
| Weight                      | 700g               |
| Inrush Current              | N/A                |
| Construction Material       | Anodised aluminium |
| UK Bathroom Zone            | 1                  |
| Electric Class (1, 2, 3)    | 3                  |
| Earth Leakage               | N/A                |
| Suitable for coastal areas  | Yes                |

## PHOTOMETRICS @ 25°C

| Product code | Finish                    | W  | Colour | Beam | lm  | lm/W | Lx @ 1m |
|--------------|---------------------------|----|--------|------|-----|------|---------|
| SL220A F NW  | Silver anodised aluminium | 3W | 4000K  | 38°  | 310 | 103  | 705     |

## WIRING INFORMATION

|                         |   |
|-------------------------|---|
| Cable / Flying Lead     | 3m H05RN-F rubberised cable (outside diameter: 6mm) |
| Type of Wiring Required | Series  |

## LED DRIVER

| Driver      | Input    | SELV | Dimming | Bathroom Zone | Min | Max |
|-------------|----------|------|---------|---------------|-----|-----|
| PLU/350 1-9 | 220-240V | Yes  | No      | 1             | 1   | 9   |
| PLU/700 3-9 | 220-240V | Yes  | No      | 1             | 3   | 9   |
| PSIP70018W  | 220-240V | Yes  | No      | 1             | 1   | 8   |

## ACCESSORIES

|                 |  |                 |
|-----------------|--|-----------------|
| JB2 / JB4 / JB6 | Waterproof junction box / Gel filled waterproof connectors               | Sold Separately |
| GH220           | Simple hood to reduce glare whilst maintaining a good light distribution | Sold Separately |
| GS220           | Stylish, baffle-style snoot, perfect for creating a moonlighting effect  | Sold Separately |



COLLINGWOOD  
LIGHTING

LIGHTING INNOVATION

3W

Equivalent to 20W halogen

Long spike included for extra stability

Robust cable for outdoor use

## WARRANTY

Warranty 1 year

## FEATURES & BENEFITS

Available in anodised aluminium

PATENT: GB2487912 GB2512715